



Control

Simplifying technology



Name: Joey Micro6

SKU: ZTT0842

Description: Pre-programmed for all major projectors and fully customizable. A wall mounted 6 button control system with LEDs. Controls IR, RS232 and contact

No programming needed:

The Joey Micro6 is by far the most advanced classroom controller available, while remaining the most cost effective. The Joey Micro is perfect for all installations from the most basic standard classroom - which could be a projector and a pull down screen only, to multi device applications including Video Conference and multi display systems.

The Joey Micro is the system of choice for the NSW DET Connected Classroom which includes 2 displays (Sanyo projector, IWB, Plasma, Tandberg Video Conference, DVD player, AUX input, Laptop and PC).

Joey Micro6 will save you money by managing your equipment. Joey Micro6 is smart enough to know when a room is empty and will shut the room down. Especially important where projectors are installed. The Joey Micro does this by tracking time, key presses and room movement.

For basic set ups, absolutely no programming is needed as the Joey Micro6 is supplied pre programmed. Simply enter the code corresponding to the projector to be controlled. For more advanced applications, using the simple, intuitive, drag and drop style Joey Editor custom graphics, orientations, macros and buttons can easily be created.

Joey Micro6 can directly control your equipment via Infra Red and RS232. This allows Joey Micro to be a complete control solution, with far more functionality than might be assumed from just 6 buttons. Because each button is context sensitive dependant on the "virtual screen", LEDs can be programmed to indicate the mode your system is in.

SPECIFICATION SHEET

Enclosure	Standard single-gang HPM wallplate
Power Supply	12v DC at 10mA (typ.) from IRBus or plugpack
Dimensions	110mm(H) x 67mm(W) x 10mm(D)
Weight	74g
Software	Joey Authoring Program
Connectivity	Connects to Access Port Via single Cat5
Programming port (3.5mm Jack)	X 1
IR Bus Phoenix Connector	X 1
Compatibility	All IR formats supported by TCS. RS232 from 300 to 38400 baud. IRBus
Cut Out Dimensions	As standard single gang wall box
Depth above mounting plane	12mm approx
Dimensions Access Port	110mm(H) x 67mm(W) x 25mm(D) (same as standard single gang wallplate)
Number of programmable keys	6 per "virtual screen"
Number of virtual screens	100 to 300 depending on application
E2 memory	32 kb
Number of loadable codesets	125